



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B65B 31/02		A1	(11) International Publication Number: WO 00/50305
			(43) International Publication Date: 31 August 2000 (31.08.00)
(21) International Application Number: PCT/IL00/00114		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 February 2000 (23.02.00)			
(30) Priority Data: 128710 ✓ 24 February 1999 (24.02.99) IL 132708 2 November 1999 (02.11.99) IL			
(71) Applicant (for all designated States except US): HEFESTUS LTD. [IL/IL]; P.O. Box 56, 30500 Byniamina (IL).		Published <i>With international search report.</i>	
(72) Inventor; and			
(75) Inventor/Applicant (for US only): YAMAI, Yehuda [IL/IL]; P.O. Box 56, 30500 Byniamina (IL).			
(74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel-Aviv (IL).			

(54) Title: PACKAGING METHOD AND APPARATUS

(57) Abstract

A method for packaging a product in a hermetically sealed container having a cup-shaped rigid or semi-rigid body with a rim fitted with a closure, the method comprising introducing the product into the cup-like shaped body (106). Forming an isolated space (204) with a gas inlet (134) and a gas outlet (112), the space defined between the body and a closure-forming member (200) adjacent to and with a clearance from the rim (107). Introducing a replacement gas through the inlet to replace at least a substantial portion of gas originally contained in the isolated space, and displacing at least one of the body or the closure-forming member towards the other of the two members to close the clearance and to attach the closure-forming member to the rim, and hermetically attaching the two to one another to form a gas-tight seal.

